

TECHNICAL SPECIFICATIONS for ACEDOORS PROCESS SLIDING DOORS

Acceptable Manufacturer

Door shall be Acedoors Process Sliding Door as supplied by AceDoor Systems 2013 Ltd.

Door Leaf

- A. 50mm thick insulated panel door leaf.
- B. Standard with 0.59BMT G2 Coloursteel panel finish.
- C. Door leaf fitted with silicone gaskets that meet food industry hygiene and safety requirements.

Door Frame

- A. Doors complete with aluminium frame.
- B. Frame includes thermal breaker strip.
- C. Standard 3-sided frame with door bottom wiper gasket.
- D. Back flashing included.

Track

- A. Standard with aluminium mill finish alloy extrusion and track.
- B. All doors complete with drop track seal assembly.
- C. Nylon wheels and handling brackets eliminate metal to metal contact.
- D. Front and Back floor guides with nylon inserts to eliminate metal to metal contact.

Hardware

- A. Standard with S/S lever handle and wall bracket.
- B. Standard with internal flush dish handle.
- C. Standard with Internal release assembly.

Options

- A. Full surround frame.
- B. Anodised aluminium extrusions.
- C. Powdercoated aluminium extrusions and track.
- D. Door leaf from:
 - a. Fire rated insulated panel.
 - b. PIR insulated panel.
- E. Full length track hood.
- F. Automatic motorised operation.
- G. Kick Plates.
- H. Chequer plate protection.
- I. Meat rail cutout.