



Built to last in the harshest conditions

Temperature sensitive with an aesthetic finish, Insulated Traffic Doors provide unparalleled longevity with an eye for style.

Insulated Traffic Doors

At home in a variety of locations, from retail to industrial. Strength and substance are matched with style, designed to keep running costs low and temperatures stable while maintaining a sleek and durable finish.

Low maintenance and engineered to the highest standards, never think about access issues again.



Key Features

Built for superior performance for use in commercial, industrial, agricultural, or loading dock applications using rugged and hard-wearing components to deliver a high-performance finish.

- ✓ **Adaptable** – Suitable for many temperature-sensitive environments including walk-in coolers, supermarkets, and hospitals.
- ✓ **Tough** – Constructed from a custom rigid P.V.C. extrusion with thermo-plastic facings and an insulated core
Insulated – Internal subframe manufactured from P.V.C. filled with P.I.R. foam
- ✓ **Attractive** – Appealing to both retail and industrial applications with a chic colour pallet of dark grey, light grey, beige, and black

Product Information

Insulated Traffic doors artfully balance style with substance, where insulation properties safeguard your temperature control and hardy construction offers longevity and durability.

- ✓ Generous sizing - Up to 2750mm High x 2400mm Wide with a 42mm thickness
- ✓ Supplied with a full perimeter gasket around the door frame, manufactured from a semi-rigid rubber strip
- ✓ Suitable for window sizes 740mm High x 235mm Wide to 540mm High x 540mm Wide
- ✓ Cushioned - Spring bumper panels or flat panels are available to cushion the impact from motorised or hand traffic vehicles



Tech Specs

MAXIMUM DOOR SIZE

Up to 2750mm High x 2400mm Wide

DOOR PANEL SPECIFICATIONS

Constructed from a custom rigid P.V.C. extrusion with thermo-plastic facings and insulated core

Side mounted top hinge system and floor mounted bottom hinge.

Outer skin ABS plastic.

Thickness: 42mm.

Colours: dark grey, light grey, beige and black.

Internal sub frame manufactured from P.V.C. filled with P.I.R. foam.

Supplied with full perimeter gasket around door frame, manufactured from a semi-rigid rubber strip.

Window Sizes: 740mm High x 235mm Wide 540mm High x 540mm Wide

Bumper Panels: Spring bumpers or flat panels are available to cushion the impact from motorised or hand traffic vehicles

Manufactured by AceDoors

Auckland: 43a Hobill Avenue, Wiri, Auckland P 0800 DOORS5

Christchurch: 12 Westland Place, Rolleston, Christchurch P 0800 DOORS1

PO Box: 76-105, Manukau, Auckland 2241, New Zealand, www.acedoors.co.nz

AceDoors - over 35 years manufacturing experience. 24/7 repair service.



**Insulated Traffic
Doors**