RAYNOR®

ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

AlumaView STANDARD, bronze-anodized

A T T R A C T I V E

D E P E N D A B L E

V I S I B L E

RAYNOR® GARAGE DOORS

Built to be worry free.™

Phone: **1-800-4-RAYNOR** Fax: **1-815-288-7142** www.raynor.com

RAYNOR®

ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

AlumaView doors have long been the standard fixture for facilities that require dependable, attractive doors that offer maximum visibility. With an anodized-finished extruded aluminum frame, AlumaView door sections are a full 1¾" or 2" thick.

AlumaView OPTIMA
Designed for peak performance and strength, this 2" thick door is available in larger sizes and features bold rail construction for maximum durability, reliability and beauty.

AlumaView STANDARD
This benchmark product provides Raynor reliability and durability to meet or exceed the requirements of daily use. With 1¾" thick door sections and streamlined rail construction, this door is engineered for lasting beauty and durability.

AlumaView STANDARD, clear-anodized, with bottom section aluminum panels

Series MODEL	Max. Opening Width	Max. Opening Height	Overall Section Thickness	Bottom Panel Thickness	End Stile Width	Center Stile Width	Colors	Warranty
AlumaView OPTIMA (HL)	24'	24'	2"	0.05"	3¼" or 6¼"	3⅝"	Clear-Anodized Finish* or 187 ArmorBrite™ Colors	1-Year
AlumaView STANDARD (L)	14'	14'	1¾"	0.05"	2⅝"	7/16"	Clear-Anodized Finish* or 187 ArmorBrite™ Colors	1-Year

*Special anodized finishes available

WARRANTY AlumaView doors carry a 1-year limited warranty. See your local Raynor Dealer for complete details.

MODEL OPTIONS AND UPGRADES



1 Choice of windows.
For maximum design flexibility, choose from tempered, tinted, double-strength, insulated, acrylic or polycarbonate glass in a variety of thicknesses.

2 187 ArmorBrite™ colors.
Choose your color! AlumaView door rails and stiles can be powdercoated in any of 187 colors for an attractive appearance and exceptional durability.

3 Aluminum panels.
For busy work environments and to prevent glass breakage, aluminum panels protect your investment.

4 High-cycle counterbalance systems.
For reliable operation in high traffic areas, choose high-cycle torsion springs with 25,000, 50,000 or 100,000-cycle life. For reduced maintenance and ultra-smooth operation in heavy-use applications, choose a weight counterbalance system.

5 Locks.
In applications where control and access are important, choose from a variety of locking options to help keep your building secure.* Locks come in both inside and outside variations.

6 Carbon monoxide vent.
Allows you to channel fumes to the outside when door is closed. Available in a variety of sizes.

7 Pedestrian doors.
Pedestrian doors are designed for convenient entry and to help minimize energy loss.*

8 Customized track and hardware systems.
Track systems are supplied to fit special clearances, inclines or contour applications. Hardware and track systems can be customized to fit any need.* Additional trussing is available for special windloading applications.

* Some options may be limited to door size or model. Contact your local Raynor Dealer regarding availability for your application.

POWERHOIST™ OPERATORS

PowerHoist operators.
Raynor offers a full line of rugged PowerHoist operators. Trolley operators (top) are mounted overhead and suspended from the ceiling. Jackshaft operators (middle) are sidemounted and attached to the side. Manual chain operation is also available.



Control options.
A variety of control stations, photoelectric eyes and remote activation devices are available.

ENERGY-SAVING OPTIONS

Header seal.
Flexible vinyl flap header seal reduces air infiltration and energy costs by sealing the top of the door against the header.

Jamb seal.
EPDM rubber jamb seal also helps to reduce air infiltration and decrease energy costs by sealing the side of the door when closed.

Every AlumaView door is built for superior performance and includes the features listed below. For additional options, please see the inside spread.

Years of durability.
Door sections are clear-anodized for maximum durability and are designed to withstand windloads up to 20 p.s.f.

Rugged hardware and springs.
Your AlumaView door comes packaged with the right combination of hardware, track and springs to match your door's size and application.

Decreased energy costs.
AlumaView doors help you reduce energy costs with a U-shaped, vinyl bottom weatherseal secured by a sturdy aluminum retainer.

(AlumaView OPTIMA model shown)

(AlumaView STANDARD model shown)

CONSTRUCTION COMPARISON

AlumaView OPTIMA
AlumaView OPTIMA panels and glass are completely encased in soft vinyl channels and held firmly in place with a rigid, snap-in retainer. This adds strength and security while reducing the chance of breakage.

AlumaView STANDARD
AlumaView STANDARD panels and glass are sealed and held in place with a snap-in retainer.

APPLICATION GUIDE

	AlumaView **OPTIMA** (HL)	AlumaView **STANDARD** (L)
Auto Dealerships	●	●
Car Wash/Corrosive Environments	●	●
Fire Station/Ambulance	●	◒
Large Opening Size	●	◒
Quick Lube Centers	●	●
Service Station	●	●
Thermal Environments	○	○
Underground Parking	○	○
Warehouse/Manufacturing	○	○

● Best Choice ◒ Good Solution ○ Applicable

Depend on Professional Installation By Your Raynor Dealer

When you select Raynor, you're not just getting a superior commercial door, you're getting professional door installation and service expertise.

Every Raynor door is installed by an experienced Raynor professional. And that means added benefits for you. Because it's done right the first time, your door will deliver performance and reliability from the day it's installed. Your technician will check your door for everything from safety to performance to appearance.

Trust your Raynor door to someone who knows it better than anyone else—your professional Raynor Dealer. We have over 600 authorized dealers serving North America and over 50 countries worldwide.

Raynor also offers a full line of rolling service, fire and traffic doors as well as security grilles and counter shutters. See your Raynor Dealer or visit www.raynor.com for more information.

AceDoors

Commercial Door Solution Specialists

ACEDOORS
43a Hobill Ave, Wiri, Auckland
Ph 09 273 4970 Fax 09 273 4972
sales@acedoors.co.nz

DASMA

This information was as complete and factual as possible at the time it was printed. We do, however, reserve the right to make changes in product specifications and availability without notice. Features and options may be different in countries other than the United States. Product colors have been reproduced as well as possible with present commercial printing processes. For absolute accuracy in color matching, use actual product samples.

© 2001 Raynor Form No. 2903484-03/01 50K (P)