

Specifications

Application	
	Internal / External
Size*	
Maximum Width	6500'
Maximum Height	6000'
Speed	
Maximum Opening Speed	2.5m/sec
Maximum Closing Speed	.6m/sec
Colour	
Standard	Silver (RAL 9006) or White (RAL 9010)
Wind Loading	
Up to	class 12 (120 kmph)
Thermal Insulation	
	K<I 5W/(m ² ·K)
Slats	
Material	Polyurethane Slat
Thickness	43mm
Finishing	Anodising & Organic Colouring
Motorisation	
Motor	Single Phase / 3 Phase Motor Drive
Motor Position	Left Hand / Right Hand
Control Panel	IP54 rated metal control box with inverter frequency controller
Control Mount	Left Hand / Right Hand
Power Supply	240 / 400v
Standard Operational Included	
Safety	Multiple Horizontal Infrared Photoeyes
	Variable Speed Control
	Encoder Control
Warranty	12 months / 6 Monthly Preventative Maintenance Programme
Counter Weight	
Systems	Spring and Chain Balancing
Extra Add Ons (Optional)	
Safety	Widescan LZR Radar with Warning Lights
Mounting Options	LH/RH
Vision Panels	Up to 3 rows
Bottom Bar	Extra Heavy Duty
Actuation	Loops, Remotes, Radar, Etc...
Interlock System	Interlock to other doors

* For larger size doors please inquire