

56 SAFEGUARD® LATCH

- Bolt-type tongue provides positive locking action Proven, heavy-duty
- construction outlasts similar latches in hard commercial
- Patented Kason adjustable strike assures precise adjustment
- Padlocking provision standard on all models
- Accepts Kason inside release lever to prevent accidental entrapment in locked walk-
- Inside lever releases cylinderlocked or padlocked door
- Unsurpassed for long life and reliability

<u>SPECIFICATIONS</u>

MATERIAL:

High pressure die-cast zinc body and strike housing, malleable iron handle. Stainless steel handle also available

See table on pg. B-8. Powder coat finishes and stainless steel handle available for use in extreme environmental conditions. Request information

MOUNTING:


Holes drilled and countersunk for 1/4" (6.0mm) screws

PACKAGING/WEIGHT: 6 body assemblies per carton/approx. 30 lb. (14kg) per carton

6 strike assemblies per carton/approx. 10 lb. (4.5kg) per carton

INSIDE RELEASE:

Order separately. See pages B-25, B-26, and B-27 for selection



5656 TWO-POINT LOCKING LATCH

Two No. 56 latches with stainless steel connecting rod. Lower latch is cylinder locking. Rod is 7/8'' (22.2mm) diameter and 37-1/4'' (946.2mm) long, sold separately. Latch has all the features of No. 56 latch. The connecting rod is provided at no-charge when ordered with the latch assembly but can be purchased separately for replacement.

SPECIFICATIONS

PACKAGING/WEIGHT: 1 per carton/approx. 13 lb. (5.9 kg)

WALK-IN

PAGE B7

KASON SAFEGUARD® LATCHES

56 SERIES ORDERING INFORMATION

Model No.	Item	Description	Finish
10056CH5020	Cylinder Locking Body	Heavy Spring	Polished Chrome
10056CH6021	Cylinder Locking Body	Heavy Spring	Brushed Chrome
10056CH0108	Cylinder Locking Body	Heavy Spring	Silver Powder Coat
10056CH8108	Cylinder Locking Body	Heavy Spring, Stainless Handle	Polished Chrome and Polished SS Handle
10056CLT108	Cylinder Locking Body	Light Spring, Stainless Handle	Silver Powder Coat Body, Polished SS Handle
10056CLT208	Cylinder Locking Body	Light Spring, Stainless Handle	Silver Powder Coat Body and Handle
10056CL5020	Cylinder Locking Body	Light Spring	Polished Chrome
10056CL6021	Cylinder Locking Body	Light Spring	Brushed Chrome
10056CL0108	Cylinder Locking Body	Light Spring	Silver Powder Coat
10056CL810805	Cylinder Locking Body	Light Spring, Stainless Handle	Polished Chrome and Polished SS Handle
10056CL902005	Cylinder Locking Body	Light Spring, Stainless Handle	Black Powder Coat Body and Handle
10056CL902205	Cylinder Locking Body	Light Spring, Stainless Handle	Black Powder Coat Body, Polished SS Handle
10056CX5020	Cylinder Locking Body	X-Light Spring	Polished Chrome
10056H05018	Padlocking Body	Heavy Spring, Stainless Handle	Polished Chrome and Polished SS Handle
10056H05020	Padlocking Body	Heavy Spring	Polished Chrome
10056H06021	Padlocking Body	Heavy Spring	Brushed Chrome
10056L0T108	Padlocking Body	Light Spring, Stainless Handle	Silver Powder Coat Body, Polished SS Handle
10056L0T208	Padlocking Body	Light Spring, Stainless Handle	Silver Powder Coat Body and Handle
10056L00086	Padlocking Body	Light Spring	Silver Powder Coat
10056L05018	Padlocking Body	Light Spring, Stainless Handle	Polished Chrome and Polished SS Handle
10056L05020	Padlocking Body	Light Spring	Polished Chrome
10056L06021	Padlocking Body	Light Spring	Brushed Chrome
10056L09022	Padlocking Body	Light Spring, Stainless Handle	Black Powder Coat Body, Polished SS Handle
10056L00086	Padlocking Body	Light Spring	Silver Powder Coat
10056XL5020	Padlocking Body	X-Light Spring	Polished Chrome
10056XL6020	Padlocking Body	X-Light Spring	Brushed Chrome
10056XL0086	Padlocking Body	X-Light Spring	Silver Powder Coat
Model No.	Item	Finish	Offset
1005600(X)00(Y)	Strike	See X Options In Table Below	See Y Options In Table Below
	X =	5 Polished Chrome Y =	2 -1/8" to 1/4" (-3.2 to 6.4 mm)
		6 Brushed Chrome	3 3/4" to 1-1/2" (19.0 to 38.1 mm)
		T Silver Powder Coat	5 1-3/4" to 2-1/2" (44.5 to 63.5 mm)
			8 3" to 4" (76.2 to 101.6 mm)
90056CM0004	Cylinder Kit for 56C models.		
		changes available. Please specify.	
A 4 I - I N I -	la	Description	Etatal.
Model No. 15656CL0004	Cylinder Locking Two Point	Description -1/8" to 1/4" (-3.2 to 6.4 mm)	Finish Polished Chrome
13030CL0004	Latch		
15656L00004	Padlocking Two Point Latch	-1/8" to 1/4" (-3.2 to 6.4 mm)	Polished Chrome